

Family Name

| |
|---|
| Model Number |
| Input AC Specifications |
| Voltage - Phase - Frequency |
| General Specifications |
| Cooling Types |
| Nominal Capacity, Tons (kw) |
| Mounting Location |
| Compressor |
| Qty |
| Location |
| Type |
| # of cooling circuits |
| Refrigerant Type |
| Physical Data |
| Unit Height, inches (mm) |
| Unit Width, inches (mm) |
| Unit Depth, inches (mm) |
| Unit Weight, lbs. (kg) |
| Feature Set |
| Blower Type |
| Air Distribution Type |
| Humidifier Type |
| Reheat Types |
| Control Type |
| Service Access |
| Heat Rejection |
| Agency/Certification/Conformance |
| Agency Approval |
| Warranty |
| Labor Standard |
| Parts Standard |
| Compressor Standard |
| Unit Standard |

For additional product models, or for more comprehensive specifications on models shown, consult product doc

Liebert Himod

HM 8, 10, 12 Tons (28, 35, 42kW)

208 - 3 - 60, 230 - 3 - 60, 460 - 3 - 60

Air, glycol, GLYCOOL, dual cool

8, 10, 12 (28, 35, 42)

Floormount

1

Unit

Scroll

1

R22, R407C

77 (1954)

68-1/2 (1740)

35 (894)

1278-1784 (580-810)

Motorized Impeller

Dn Flow -Underfloor, Up-Flow -Duct, Up-Flow -Plenum Grill

Canister

3-stage electric

AM/AG

Front

Condenser, Drycooler, Closed loop water tower

CSA per UL1995, MEA

90 days after start-up; 1 year optional

1 Year

1 Year

1 Year

Documentation or contact your Liebert representative.